ASTM ANSI CUT LEVEL A3

Dry | Wet | Heat | Oily | Cold | Chemical

EN 388:2016 4 X 4 4 C

TG5170

A lightweight X-Dura Flat Nitrile palm coated Cut C glove with high stretch comfort liner and generous cuff length.. Delivering good cut protection, extended wear life and all day comfort.

Key Features

- Breathable seamless liner with added spandex for a close fit
- Generous knit wrist to protects hand from dust and dirt
- Palm dipped flat nitrile coating for unrivalled grip in dry conditions
- High protection against mechanical risk

Ideal for

- Automotive
- Construction and Utility
- Engineering and Manufacturing
- Warehousing and Logistics
- Waste, Recycling and Local Authority

Sizes:	6-11	**Gauge:**	13gg
Liner:	Polyamide/PPE/ Glass/Elastane	**Coating:**	X-Dura Nitrile
No/Bag:	10	**No/Carton:**	100

Traffi®
THE HAND PROTECTION **SPECIALISTS**

www.traffiglove.com

TG5170

Glove Specifications

Glove lengths
220mm-270mm

Glove Weight
13 gauge

Liner Type
Polyamide/HPPE/Glass fibre/Elastane

Glove colour
Pantone 368c / R:92 G:193 B:81 / C:63 M:0 Y:100 K:0

Overlock Colours

SIZE	XS-6	S-7	M-8	L-9	XL-10	2XL-11	3XL-12
COLOUR	BLUE	RED	ORANGE	WHITE	YELLOW	BLACK	GREEN

Coating Specifications

Coating colour
Black

Dip type
X-Dura Flat Nitrile

Dip Application
Palm Dipped

Glove Treatment
X-Dura

Packaging Information

Qty/bag
10 pairs

Qty/carton
100 pairs

Carton Dimensions
290mm x 440mm x 280mm

Maintenance

Both new and used gloves should be inspected to ensure no damage is present prior to use. A light gentle wash up to 3 washing cycles with mild detergent without involvement of any sort of bleaching agents. No tumble drying, just line dry at low temperature up to 30 degree Celsius.

Storage
Gloves should be ideally stored in cool, dry conditions away from excessive heat and in its original packaging.

Disposal
Used protective gloves can be contaminated or infected with harmful substances. Dispose of the gloves as instructed by your local authority.

Traffi®
THE HAND PROTECTION **SPECIALISTS**

www.traffiglove.com