



Dry



Wet



Heat




Oily



Cold



Chemical



TG535

A comfortable Cut Level C glove with an X-Dura Nitrile Foam palm dipped coating. Excellent grip and a full length cuff for use in wet and dry conditions.

Key Features

- High stretch yarn for enhanced fit and dexterity
- Great protection against mechanical risk
- Effective palm dip coating suitable for multiple conditions

Ideal for

- Automotive
- Construction and Utility
- Metalworking
- Engineering and Manufacturing
- Oil and Gas
- Packaging

Sizes:	6-11	Gauge:	13gg
Liner:	Polyamide/PPE/Glass	Coating:	X-Dura Nitrile
No/Bag:	10	No/Carton:	100

TG535

Glove Specifications

Glove lengths
220mm-270mm

Glove Weight
13 gauge

Liner Type
Polyamide/HPPE/Glass fibre

Glove colour
Pantone 368c / R:92 G:193 B:81 / C:63 M:0 Y:100 K:0

Overlock Colours

SIZE	XS-6	S-7	M-8	L-9	XL-10	2XL-11	3XL-12
COLOUR	BLUE	RED	ORANGE	WHITE	YELLOW	BLACK	GREEN

Coating Specifications

Coating colour
Black

Dip type
X-Dura Nitrile Foam

Dip Application
Palm Dipped

Glove Treatment
X-Dura



Packaging Information

Qty/bag
10 pairs

Qty/carton
100 pairs

Carton Dimensions
290mm x 440mm x 280mm

Maintenance

Both new and used gloves should be inspected to ensure no damage is present prior to use. A light gentle wash up to 3 washing cycles with mild detergent without involvement of any sort of bleaching agents. No tumble drying, just line dry at low temperature up to 30 degree Celsius.

Storage

Gloves should be ideally stored in cool, dry conditions away from excessive heat and in its original packaging.

Disposal

Used protective gloves can be contaminated or infected with harmful substances. Dispose of the gloves as instructed by your local authority.